

## Power-PRO™ XT Cot sole source information

To whom it may concern,

Stryker certifies that we are the sole manufacturer of Stryker's Power-PRO XT Cot (Model 6506). This correspondence is to inform you of the characteristics of the Power-PRO Cot. These characteristics can be broken down into two primary categories: **qualifications** and **ease of use**.

**Qualifications:**

- IPX6: The system is tested to withstand powerful water jets.
- IEC 60601-1 and IEC 60601-1-2: The Power-PRO XT Cot conforms to industry standards for mechanical and electrical safety for medical electrical devices, as well as electromagnetic compatibility and immunity.
- BS EN-1789:2007, clause 4.5.9 when used with Power-LOAD Cot Fastener and X-Restraints: This is a European dynamic crash test which subjects a 50th percentile dummy to nominal 10g deceleration for a minimum of 50ms. Following the test there shall be no sharp edges.
- Meets SAE J3027 dynamic crash test safety standards when used with Power-LOAD/Performance-LOAD Cot Fastener and X-Restraints.

**Ease of use:**

- The cot has a weight capacity of 700 lb.
- When unloading with the manual release handle, the cot utilizes hydraulic dampening. Thus, the cot will not abruptly jar the operator or patient.
- The battery is placed at the foot end of the stretcher.
- The cot legs power-retract in 3.5 seconds which speeds load time.
- The cot provides a load height of 36" and is operator adjustable to match the deck height of individual ambulances.
- The foot-end of the cot provides lifting bars and operator controls at two different heights, thus providing optimal ergonomics to most operator heights.
- The foot end of the cot contains a large battery indicator light which displays amber or green which indicates battery level. A warning is given by a flashing amber light, providing the operator the time to change the battery before full depletion of power.
- The Model 6506 has 6" x 2" sealed casters and bearings.
- The cot features a foot end mounted hourly usage meter. This tool can be used to determine the timing of preventative maintenance checks.
- The cot features powder-coating of the aluminum frame (including the patient handling surfaces) and sealed caster bearings, thus reducing aluminum oxidation throughout the cot.
- The cot is power washable.

Please contact your Sales Representative for further information.

Sincerely,



John Guyeskey, Sr. Manager, Downstream Marketing

Stryker or its affiliated entities own, use, or have applied for the following trademarks or service marks: Performance-LOAD, Power-LOAD, Power-PRO, Stryker. All other trademarks are trademarks of their respective owners or holders. The absence of a product, feature, or service name, or logo from this list does not constitute a waiver of Stryker's trademark or other intellectual property rights concerning that name or logo. Copyright © 2022 Stryker. M0000001063 REV AB

**Emergency Care**

3800 E. Centre Avenue, Portage, MI 49002 USA | P +1 269 329 2100 | Toll-free +1 800 327 0770 | [stryker.com](https://www.stryker.com)